

Product Group: T-304 Stainless Steel Tensile Bolting Cloth 200 x 200 Mesh, 0.0016" Dia.

Trade Name:	200 Mesh, 0.0016" TBC		
Mesh Count:	200 x 200	Tolerance:	Warp +/- 2% Shute +/- 4%
C-C Pitch:	0.0050" (0.1270mm)		
Wire Diameter:	0.0016" (0.04064mm)	Tolerance:	+/- 0.0001" (0.003mm)
Total Thickness:	0.0032" (0.08128mm)		
Material:	T-304 Stainless Steel	Standard:	ASTM A555-79
Weave Type:	Plain Weave	Standard:	ASTM E2016-06

Opening Size:	0.00340" (86 Microns)	Across Diagonal:	0.0048083263" (122 Microns)
Perimeter:	0.01360" (0.34544mm)	Open Area Per sq/ft:	66.58560" (1691.27424mm)
Area of Opening:	0.00001156" (0.000293624mm)	Openings Per sq/in:	40000
Open Area:	46.2%	Wire Surface Area:	53.8%

Weight:	0.035 lbs/sq.ft. 0.171 kg/sq.m		
Full Roll Length:	100 Feet (30.48M)	Length Tolerance:	+/- 10%
Std. Roll Widths:	48" - 60"	Width Tolerance:	+/- 1/8" (3.18mm)
Custom Widths:	Slit according to customer requirements		

Technical data and statistical information contained in this document have been derived from industry standards. Although we believe that the information supplied is generally correct, we do not assume any responsibility whatsoever for its accuracy. Users of this data sheet do so at their own risk.

When quality counts... Make it Marco!