

Product Group: Micronic Filter Cloth

20 x 250 Micronic Filter Cloth T-304 Stainless Steel

<b>Warp Mesh Count:</b>	20	<b>Tolerance:</b>	+/- 2%
<b>C-C Pitch:</b>	0.0500" (1.2700mm)		
<b>Wire Diameter:</b>	0.0098" (0.1778mm)	<b>Tolerance:</b>	+/- 0.0003" (+/- 0.008mm)
<b>Weft Mesh Count:</b>	250	<b>Tolerance:</b>	+/- 4%
<b>C-C Pitch:</b>	0.0040" (0.1016mm)		
<b>Wire Diameter:</b>	0.0079" (0.2007mm)	<b>Tolerance:</b>	+/- 0.0002" (+/- 0.005mm)
<b>Total Thickness:</b>	0.0270" (0.6900mm)		
<b>Material:</b>	T-304 Stainless Steel	<b>Standard:</b>	ASTM A555-79
<b>Weave Type:</b>	Twill Dutch Weave	<b>Standard:</b>	ASTM E2016-06
<b>Nominal Retention:</b>	100 Microns (0.0039")	<b>Absolute Retention:</b>	110-120 Microns (0.0045") (115 Mic)
<b>Weight:</b>	0.684 lbs/sq.ft. 3.34 kg/sq. m		

**Supply Criteria**

<b>Full Roll Length:</b>	100 Feet (30.48M)	<b>Length Tolerance:</b>	+/- 10%
<b>Std. Roll Widths:</b>	48" - 60"	<b>Width Tolerance:</b>	+/- 1/16" (1.6mm)
<b>Custom Widths:</b>	Can be slit according to customer requirements		

Technical data and statistical information contained in this document have been derived from industry standards. Although we believe that the information supplied is generally correct, we do not assume any responsibility whatsoever for its accuracy. Users of this data sheet do so at their own risk.

*When quality counts... Make it Marco!*