

Product Group: Market Grade Wire Mesh

16 x 16 Mesh x 0.018" Dia.

Mesh Count:	16 x 16	Tolerance:	Warp +/- 2% Shute +/- 5%
C-C Pitch:	0.06250" (1.58750mm)		
Wire Diameter:	0.018" (0.4572mm)	Tolerance:	+/- 0.0004" (0.010mm)
Total Thickness:	0.036" (0.9144mm)		
Weave Type:	Plain Weave	Standard:	ASTM E2016-06

Opening Size:	0.04450"	Across Diagonal:	0.0629325035"
Perimeter:	0.1780"	Open Area Per sq/ft:	72.999936"
Area of Opening:	0.00198025" (0.05029835mm)	Openings Per sq/in:	256
Open Area:	50.7%	Wire Surface Area:	49.3%

Weight:	0.348 lbs/sq.ft. 1.699 kg/sq. m		
Full Roll Length:	100 Feet (30.48M)	Length Tolerance:	+/- 10%
Std. Roll Widths:	36" - 48" - 60"	Width Tolerance:	+/- 1/8" (3.2mm)
Custom Widths:	Can be slit according to customer requirements		

Technical data and statistical information contained in this document have been derived from industry standards. Although we believe that the information supplied is generally correct, we do not assume any responsibility whatsoever for its accuracy. Users of this data sheet do so at their own risk.

When quality counts... Make it Marco!